

DSMH15LED-WGF

DSMH15LED-WGF

Panel Type	15"(4:3) LED Monitor Glass Fronted
Case Type	Metal
Maximum Resolution	1024 (H) x 768 (V)
Active Display Area	304.128 x 228.096 (V) mm
Pixel Pitch	0.297 (H) x 0.297 (V) mm
Bezel Thickness	Side: 14.75mm Top: 17.25 Bottom: 17.25mm
Contrast Ratio	700:1
Brightness	350 cd/ m ²
Response Time	8ms
Viewing Angle	U/D: 65° / 60°, L/ R: 70° / 70°
Display Colours	16.7 M
Video Synchronization	Yes
PC Compatible Frequency	30-80KHz(H) / 50-75Hz(V) Max. 1024 x 768
Adjustable Colour Temperature	9300K / 6500K / 5800K / User
Video Compatibility	Multi-Standard for NTSC / PAL
Aspect Ratio	4:3 Ratio with 16:9 Option
VGA Auto Frequency correction	Yes
Speaker	Multimedia Speakers
Number of Speakers	Right x 1 Left x 1, 2.5W
Sound Demodulation	Stereo, Audio
Mute	Yes
Work Humidity	20 % - 70 %
Work Temperature	- 10 to 50 °C
Volume +/- Power On/Off	Yes

IN/OUT INTERFACE

Video Interface	HDMI x1 VGA x 1 BNC x 2 In / BNC x 1 Out
Audio Interface	Audio in x 1, Audio L x 1, Audio R x 1
Power Interface	DC In x 1
Termination	75 Ohms (Automatic termination)
Safety & EMC Certification	Energy Star / CE / FCC / ROHS/ E13
Vesa Standard Mount	100 x 100mm
Stand Type	Picture Frame
Colour	Black
Button Position	Right Hand Side
Packing Dimension	410 (W) x 410 (H) x 142 (D) mm
NET Weight	3.8 Kg
GROSS Weight	4.8 Kg



POWER

Power Supply	12VDC, 3amp
Voltage	AC100 - 240V 50 / 60Hz
Power Consumption	<18W in ON Mode

OSD CONTROLS

Contrast, Brightness, OSD Duration, H-Position, V-Position, Language, Picture Mode, Color Temp, Scale, Saturation, Backlight, Sleep Timer, Sound, Memory Recall.

OSD LANGUAGE

English, French, German, Spanish, Italian, Russian, Polish and Portuguese

ACCESSORIES

Power Supply / Kettle Lead
HDMI Cable / Remote Control / User Manual



